

Package ‘esreg’

January 9, 2019

Type Package

Title Joint Quantile and Expected Shortfall Regression

Version 0.4.0

Date 2019-01-09

Description

Simultaneous modeling of the quantile and the expected shortfall of a response variable given a set of covariates, see Dimitriadis and Bayer (2017) <arXiv:1704.02213>.

License GPL-3

Encoding UTF-8

LazyData true

Imports quantreg, Rcpp, stats, Formula

LinkingTo Rcpp, RcppArmadillo

RoxygenNote 6.1.0

NeedsCompilation yes

Author Sebastian Bayer [aut, cre],
Timo Dimitriadis [aut]

Maintainer Sebastian Bayer <sebastian.bayer@uni-konstanz.de>

Repository CRAN

Date/Publication 2019-01-09 21:10:03 UTC

R topics documented:

esreg	2
esr_loss	4
vcov.esreg	4
vcovA	5
vcovB	5

Index	7
--------------	----------

esreg

*Joint Quantile and Expected Shortfall Regression***Description**

Estimates a joint linear regression model for the pair (VaR, ES):

$$Q_{\alpha}(Y|Xq) = Xq'\beta_q$$

$$ES_{\alpha}(Y|Xe) = Xe'\beta_e$$

Usage

```
esreg(...)

## S3 method for class 'formula'
esreg(formula, data = parent.frame(), alpha, g1 = 2L,
      g2 = 1L, early_stopping = 10, ...)

## Default S3 method:
esreg(xq, xe, y, alpha, g1 = 2L, g2 = 1L,
      early_stopping = 10, ...)
```

Arguments

...	Further arguments (does not apply here)
formula	Formula: $y \sim x1 + x2 \dots x1 + x2 \dots$ where the first part after the response variable specifies the quantile equation and the second the expected shortfall part. If only one set of regressors is provided it is used for both model specifications.
data	data.frame that holds the variables
alpha	Probability level
g1	1, 2 (see G1_fun , G1_prime_fun), defaults to 1
g2	1, 2, 3, 4, 5 (see G2_curly_fun , G2_fun , G2_prime_fun). defaults to 2
early_stopping	Stop the iterated local search if there is no improvement in early_stopping steps.
xq	Explanatory variables for the quantile regression equation
xe	Explanatory variables for the expected shortfall regression equation
y	Response vector

Value

An esreg object

References

[A Joint Quantile and Expected Shortfall Regression Framework](#)

See Also

[vcov.esreg](#) for covariance estimation

Examples

```
# Simulate data (DGP-(2) in the linked paper)
set.seed(0)
x <- rchisq(1000, df=1)
y <- -x + (1 + 0.5 * x) * rnorm(1000)

# True quantile and expected shortfall regression parameters (for alpha=0.025)
alpha=0.025
true_pars <- c(-1.959964, -1.979982, -2.337803, -2.168901)

# Estimate the model using the standard settings
fit <- esreg(y ~ x, alpha=alpha)

# Compare the different variance-covariance estimators
cov1 <- vcov(object=fit, sparsity="iid", cond_var="ind")
cov2 <- vcov(object=fit, sparsity="nid", cond_var="scl_N")
cov3 <- vcov(object=fit, sparsity="nid", cond_var="scl_sp")

print("Comparison of the variance-covariance estimators")
print(rbind(Truth=true_pars,
            Estimate=coef(fit),
            SE_iid_ind=sqrt(diag(cov1)),
            SE_nid_N=sqrt(diag(cov2)),
            SE_nid_sp=sqrt(diag(cov3))))

# Compares estimates using different G2 functions
fit1 <- esreg(y ~ x, alpha=alpha, g2=1)
fit2 <- esreg(y ~ x, alpha=alpha, g2=2)
fit3 <- esreg(y ~ x, alpha=alpha, g2=3)
fit4 <- esreg(y ~ x, alpha=alpha, g2=4)
fit5 <- esreg(y ~ x, alpha=alpha, g2=5)
fits <- sapply(list(fit1, fit2, fit3, fit4, fit5), coef)
colnames(fits) <- sapply(1:5, function(i) esreg::.G_function_names(1, i)[2])
print("Comparison of the five G2 functions")
print(rbind(Truth=true_pars, t(fits)))

# Usage of different covariates
x <- rchisq(1000, df=1)
noise <- rnorm(1000)
y <- -x + (1 + 0.5 * x) * rnorm(1000)
fit <- esreg(y ~ x | x + noise, alpha=0.025)
print("Using different covariates for VaR and ES")
print(summary(fit))
```

esr_loss *Joint Loss Function*

Description

Computes the joint (VaR, ES) loss

Usage

```
esr_loss(r, q, e, alpha, g1 = 2L, g2 = 1L, return_mean = TRUE)
```

Arguments

r	Vector of returns
q	Vector of quantiles
e	Vector of expected shortfalls
alpha	Probability level
g1	1, 2, see G1_fun
g2	1, 2, 3, 4, 5, see G2_curly_fun , G2_fun
return_mean	If TRUE returns the average tick loss, else the individual values

References

Fissler and Ziegel (2016)

vcov.esreg *Covariance Estimation*

Description

Estimate the variance-covariance matrix of the joint (VaR, ES) estimator

Usage

```
## S3 method for class 'esreg'
vcov(object, method = "asymptotic", ...)
```

Arguments

object	An esreg object
method	For asymptotic use vcovA , for boot use vcovB
...	All possible values which can be passed to vcovA and vcovB

vcovA

Asymptotic Covariance Estimation

Description

Estimate the variance-covariance matrix of the joint (VaR, ES) estimator using the asymptotic formulas

Usage

```
vcovA(object, sparsity = "iid", cond_var = "ind",
       bandwidth_type = "Hall-Sheather")
```

Arguments

object	An esreg object
sparsity	The sparsity estimator, see density_quantile_function for more details. <ul style="list-style-type: none"> • iid - Piecewise linear interpolation of the distribution • nid - Hendricks and Koenker sandwich
cond_var	The conditional truncated variance estimator, see conditional_truncated_variance for more details. <ul style="list-style-type: none"> • ind - Variance over all negative residuals • scl_N - Scaling with the normal distribution • scl_sp - Scaling with the kernel density function
bandwidth_type	The bandwidth estimator <ul style="list-style-type: none"> • Bofinger • Chamberlain • Hall-Sheather

vcovB

Bootstrap Covariance Estimation

Description

Estimate the variance-covariance matrix of the joint (VaR, ES) estimator using the bootstrap.

Usage

```
vcovB(object, bootstrap_method = "iid", B = 1000)
```

Arguments

object	An esreg object
bootstrap_method	The bootstrap sampling scheme to be used <ul style="list-style-type: none">• iid - The iid bootstrap of Efron (1979)
B	The number of bootstrap iterations

Index

`conditional_truncated_variance`, [5](#)

`density_quantile_function`, [5](#)

`esr_loss`, [4](#)

`esreg`, [2](#)

`G1_fun`, [2](#), [4](#)

`G1_prime_fun`, [2](#)

`G2_curly_fun`, [2](#), [4](#)

`G2_fun`, [2](#), [4](#)

`G2_prime_fun`, [2](#)

`vcov.esreg`, [3](#), [4](#)

`vcovA`, [4](#), [5](#)

`vcovB`, [4](#), [5](#)